

DHI-PHROA3.91-RCL

General Outdoor Rental LED



Features :

- Support the interconnection of 90° splicing (customized)
- Equipped with quick locking buckle, easy to operate.



Technical Specification

Model

Model DHI-PHROA3.91-RCL

Parameters

Pixel Pitch	3.91mm
Pixel Type	1R1G1B
Pixel Configuration	SMD1921
Brightness(Max)	4500 nit
Color Temperature	3000K-10000K (adjustable)
Viewing Angle	H140°/V120°
Pixel Density	65,536 dots/m ²
Module Size	W250mmxH250mm
Module Resolution	64x64 dots
Cabinet Size	W500xH1000xD70mm
Cabinet Resolution	128x256 dots
Cabinet Weight	12kg ± 0.5
Cabinet Material	Die-cast aluminum

Cabinet Aspect Ratio	1:2
IP Rating	Front IP65/Rear IP54
Operating Temperature/Humidity	-20 C~+50 C /10%~80%RH
Storage Temperature/Humidity	-20 C~+60 C /10%~90%RH
Gray Scale	14 bits
Contrast Ratio	5000:1
Refresh Rate	3840 Hz
Input power frequency	50/60 Hz
Input Voltage	AC200~240V (+/-10%)
Input Power (Max)	800 W/ m ²
Input Power (Avg)	400 W/ m ²
Installation Mode	Floor Mounted/Hanging
Maintenance Mode	Rear maintenance
Signal Transmission Distance	CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km)